



T&T SALVAGE

USA +1 281 446 4010 • Singapore +65 6591 5288

www.ttsalvage.com • info@ttsalvage.com

24 Hour Emergency Response +1 713 534-0700

HYDRAULIC SUBMERSIBLE PUMPS AND DEWATERING PUMPS

MSP-700		TK-150	
Capacity	3,218 GPM	Capacity	1,800 GPM
Head	495 feet	Head	344 feet
Discharge	6"	Discharge	6"
Products	Foodstuff, Molasses, fuel oil, salvage	Products	Fuel oil, salvage
		Will fit through a standard Butterworth opening	
MSP-300		MSP-65-315 MONO	
Capacity	1,455 GPM	Capacity	375 GPM
Head	344 feet	Max. Pressure	174 psi
Discharge	4"	Discharge	4"
Products	Foodstuff, Molasses, fuel oil, salvage	Products	High viscous material
Will fit through a standard Butterworth opening		Will fit through a standard Butterworth opening	
6" Booster Pump		S6P	
Capacity	900 GPM	Capacity	1,200 GPM
Discharge	6"	Head	20 feet
Hyd. Input	35 GPM	Discharge	6"
Max Pressure	174 psi (at discharge)	Hyd. Input	8 GPM
S3TC			
Capacity	450 GPM		
Head	45 feet		
Discharge	3"		
Hyd. Input	8 GPM		

HYDRAULIC POWER UNITS

TT-70		DHP-280	
Capacity	70 GPM	Capacity	70 GPM
Operates	1 x MSP-700 or 1 x TK-150	Operates	1 x MSP-700 or 1 x TK-150
	2 x MSP-300 or MSP 65-315		2 x MSP-300 or MSP 65-315
Weight	5,000 pounds dry	Weight	2,800 pounds dry
DHP-120		DHP-EX-200 (Zone 2 Class Approved)	
Capacity	35 GPM	Capacity	53 GPM
Operates	1 x MSP-300 or MSP 65-315	Operates	1x MSP-700 or 1 x TK-150
			2 x MSP-300 or MSP 65-315
Weight	1,985 pounds dry	Weight	2,400 pounds dry
TTHP-12			
Capacity	12 GPM		
Operates	1 x or 1 x S6P		
Weight	1,985 pounds dry		

