



T&T SALVAGE

USA +1 281 446 4010 • Singapore +65 6591 5288

www.ttsalvage.com • info@ttsalvage.com

24 Hour Emergency Response +1 713 534-0700

FIRE PUMPS

TT-1400

Capacity	6,000 GPM @ 170 psi
Monitors	3 x 4"
Hose Connections	2 x 5", 8 x 2.5"
Weight	17,000 lbs
Throw Distance	300 feet



TT-750

Capacity	3,300 GPM @ 190 psi
Monitors	1 x ALCO HR 377
Booster Pump	3,300 GPM @ 30' head
Hose Connections	5 x 2.5", 3 x 1.5"
Foam Induction	0-6%
Weight	5,400 lbs
Throw Distance	450 feet



TT-600

Capacity	2,650 GPM @ 190 psi
Monitors	2 x ALCO HR 376
Hose Connections	5 x 2.5", 3 x 1.5"
Foam Proportioner	Around the pump 0-6%
Weight	6,600 lbs
Throw Distance	300 feet



Placing two units on a vessel meets the pumping requirements for a Class A fire boat.

TT-450

Capacity	2,000 GPM @ 200 psi
Monitors	1 x 4"
Hose Connections	3 x 2.5"
Foam Induction	In-Line
Weight	2,500 lbs
Throw Distance	300 feet

