



T&T SALVAGE

USA +1 281 446 4010 • Singapore +65 6591 5288

www.ttsalvage.com • info@ttsalvage.com

24 Hour Emergency Response +1 713 534-0700

PORTABLE NITROGEN GENERATOR N2G-500

Capacity – One Unit	500 m ³ /hour @ 8 bar 17,657 ft ³ /hour @ 116 psi
Capacity – Two Units	1,000 m ³ /hour @ 8 bar 35,314 ft ³ /hour @ 116 psi
Gas Composition	
	Oxygen 1 to 5%
	Nitrogen + Argon 95% to 99%
Dew Point	-60° C / -76° F
Electric supply	440V/3 Phase/60 Hz 400V/3 Phase/50 Hz
Dimensions per unit	62.4" x 38" x 101" (1584 mm x 964 mm x 2565 mm)
Weight Per Unit	2,500 pounds (1133 Kg)
Additional Equipment - One Unit	
	Air Dryer and Compressor 23 m ³ /minute (812 ft ³ /minute)
Additional Equipment - Two Units	
	Air Dryer and Compressor 45 m ³ /minute (1,590 ft ³ /minute)

Lloyd's certified designed and built in accordance with the regulations of IMO for shipboard use and outdoor operation.

Units are completely portable and can be air freighted to any location in the world. Units can be used as separately or paired together for double capacity.

Units are located in Houston, Texas USA and Singapore.

A T&T operator is required with this equipment.

