



T&T MARINE SALVAGE, INC.

9723 Teichman Road • Galveston, Texas 77554

Phone: +1 (409) 744-1222 • Fax: +1 (409) 744-5218

www.teichmangroup.com • info@teichmangroup.com

N2G-500

PORTABLE NITROGEN GENERATOR

SPECIFICATIONS

CAPACITY – ONE UNIT

500 m³/HOUR @ 8 Bar

17,657 ft³/HOUR @ 116 PSI

GAS COMPOSITION

OXYGEN

1 to 5%

NITROGEN + ARGON

95% to 99%

DEW POINT

-60° C / -76° F

ELECTRIC SUPPLY

440V/3 PHASE/60 Hz

400V/3 PHASE/50 Hz

DIMENSIONS

62.4" x 38" x 101" (1584 mm x 964 mm x 2565 mm)

WEIGHT

2,500 POUNDS (1133 Kg)

ADDITIONAL EQUIPMENT

AIR DRYER AND COMPRESSOR

23 m³/MINUTE

812 ft³/MINUTE

LLOYD'S CERTIFIED, DESIGNED AND BUILT IN ACCORDANCE WITH THE REGULATIONS OF IMO FOR SHIPBOARD USE AND OUTDOOR OPERATION.

UNITS ARE COMPLETELY PORTABLE AND CAN BE AIR FREIGHTED TO ANY LOCATION IN THE WORLD. UNITS CAN BE SHIPPED ON THEIR SIDE TO MINIMIZE HEIGHT REQUIREMENTS.

UNITS CAN BE USED SEPERATELY OR PAIRED FOR INCREASED CAPACITY.

UNITS ARE LOCATED IN HOUSTON, TEXAS (USA) AND ROTTERDAM (THE NETHERLANDS).

A T&T OPERATOR IS REQUIRED WITH THIS EQUIPMENT.

